

# 19" TFT LCD



As dependable in the air as on the ground

The 19" TFT LCD monitor gives you high quality picture even in extreme environments. It is fully certified for airborne applications and proven reliable in tests of extreme temperatures, shocks, high/low pressure and decompression. It also comes with smart functions like programmable keys, a kill switch for the backlight and a slave function that allows you to send the image feed to an additional monitor.

### Guaranteed performance

Our products always come with lifetime support to ensure your equipment maintains peak performance for many missions to come.

#### Technical Specification

Description	19" TFT LCD, Max resolution 1280 x 1024 Heater for expanded temperature range, minimum startup temp -40 °C
Buttons (front)	5 functional keys Quick button for shutdown of backlight to "zero"
Interfaces (rear)	In: DVI+RGB+Composite, Glenair 803-005-02NF 12-37PN
Power	DC: 1 8-32 V, MIL-1275B, D38999/20-26WB02PN
Chassi	Aluminium
Dimension	439 x 383 x 74 mm (W x D x H)
Weight	10 kg

#### Environmental specification

Operating Temperature	0 °C to 55 °C
Storage Temperature	-40 °C to 70 °C



Building 9, 257 Jean Avenue  
Central Office Park  
Centurion  
South Africa  
Tel +27 12 664 4515, Fax +27 12 644 0302  
email info-cs@cstream.co.za  
www.cstream.co.za



ISO 9001: Certificate No. FM68727  
ISO 14001: Certificate No. EMS54313



www.mildef.com